



BAVARIAN AUTOSPORT

Ellipsoid Headlight Cover Installation Instructions

ATTENTION: The instructions on the package are incorrect. The following installation instructions are to be followed in place of the instructions printed on the product package.

325e/i

88 thru 5/89

525i

535i

M5

89 thru 96
with or without
ellipsoid lights

735i/il **750il**

88 thru 94
with or without
ellipsoid lights

PART NUMBER:

40 575E 5-3/4" Ellipsoid or Non-sealed Beam Headlights

PARTS INCLUDED:

(4) 5-3/4" Lexan Headlight Covers

PROCEDURE:

1. Do not remove the headlight trim rings.
2. If clearance is too tight between the trim ring and the surrounding grill, then it may be necessary to remove the grill.
3. Lubricate inside lip of cover using diluted dish soap and water, but be careful not to apply too much as it could drip onto the lens portion of cover and leave a mark when it dries.
4. Center cover over light and push on the center of the cover so that it slides over trim ring evenly all around. *NOTE: The cover must go on evenly or it will not go over the trim ring.*
5. Reinstall grills, if they were removed.



275 Constitution Avenue, Portsmouth, NH 03801

Call Toll Free: **1.800.535.2002**

• 603.427.2002 • Fax 800.507.2002 • www.bavauto.com