

**BAVARIAN AUTOSPORT**

# E34 Clear or Smoke Parking Lights Installation Instructions

**SAFETY WARNING:** Be sure the ignition switch and light switch are in the **OFF** position before removing or attaching any electrical connectors.

**NOTE:** The european lens units may come with a single filament bulb holder and single filament amber bulb already installed. These are not to be used. They should be removed and discarded.

## 5 Series

89 thru 96

**PART NUMBER:**

E34 PCLR or E34 PSMK

**PROCEDURE:**

1. Open the engine hood. Remove the black plastic protective covers from behind the headlight assemblies.
2. Remove the harness plugs from the bulb holder sockets at the back of the parking light assemblies.
3. Remove the three phillips head screws securing each parking light assembly, from behind. Push the assemblies forward and remove them.
4. Remove the bulb holder sockets from the original parking light assemblies and remove the dual filament bulbs, (they will not be used). Remove the bulb holder sockets from the new parking light assemblies and discard them. Install the amber dual filament bulbs (supplied) into the original bulb holder sockets. Install the original bulb holder sockets into the new parking light assemblies.
5. Reinstall the new parking light assemblies into the car. Plug the wiring harnesses into the bulb holders. Reinstall the black plastic headlight covers.



Call Toll Free: **1.800.535.2002**